



SD60 specifications



Builder Model	<ul style="list-style-type: none"> • EMD SD60
Nominal Dimensions	<ul style="list-style-type: none"> • Length Between Couplers: 71' 2" • Distance Between Bolster Centers: 59' 5.5" • Height - Cab Roof to Top of Rail: 15' 7.5" • Truck Wheel Base: 13' 7"
Main Components	<ul style="list-style-type: none"> • 16-710G3A Prime Mover • AR11A - Main Traction alternator • 26L Airbrake
Drive	<ul style="list-style-type: none"> • Traction Motors: 6 • Model: D87B • Gear Ratio: 77:17 • Wheel Diameter: 40"
Weights and Capacities	<ul style="list-style-type: none"> • Nominal Weight: 389,500 lbs • Fuel Tank Capacity: 4,400 gals • Sand: 56 cu ft • Cooling Water: 250 gals • Lubricating Oil: 283 gals
Performance	<ul style="list-style-type: none"> • Minimum Continuous Speed: 9.8 mph • Continuous Tractive Effort: 100,100 lbs • Starting Tractive Effort: 120,000 lbs • Maximum Locomotive Speed: 70 mph
Horsepower	<ul style="list-style-type: none"> • Engine Speed: 904 rpm • Tractive Horsepower: 3,800
Build Date	<ul style="list-style-type: none"> • 1987
Additional Equipment	<ul style="list-style-type: none"> • Air Conditioning • AESS • Ditch lights front and rear • Extended Range Dynamic Brake

About CIT

CIT's rail division offers a full suite of railcar leasing and equipment financing solutions to rail shippers and carriers across North America. It manages one of the youngest and most diversified railcar and locomotive fleets in the industry and leverages its deep experience to empower customers to succeed and prosper.

CIT is a leading national bank focused on empowering businesses and personal savers with the financial agility to navigate their goals. CIT Group Inc. (NYSE: CIT) is a financial holding company with over a century of experience, and operates a principal bank subsidiary, CIT Bank, N.A. (Member FDIC, Equal Housing Lender).

Get in touch

30 South Wacker Drive, Suite 2900
Chicago, IL 60606

Ken Pierson
312-906-5790
ken.pierson@cit.com